






COMPACT flow measuring device

- For continuous multiparameter monitoring
- Measuring and monitoring of flow, temperature and conductivity
- Quick and flexible start-up via IO-Link and wireless short-distance communication via radio waves
- Easy adjustment to suit the process by using adapters

Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with

- | | |
|---|--|
|  | Type 8619 ▶
multiCELL - Multi-channel and multi-function transmitter/controller |
|  | Type 8611 ▶
eCONTROL - Universal controller |
|  | Type 8025 ▶
Insertion flowmeter/ batch controller with paddle wheel and flow transmitter/remote batch controller |

Type description

The Type 8050 is a compact magnetic-inductive flow measuring device that will help you monitor your processes. Thanks to its compact and robust design, this device is the perfect solution for applications where space needs to be saved. Additional connection adapters enable smooth integration into the process and the wireless connection facilitates starting up the device.



Table of contents

1. General technical data	3
2. Approvals	6
2.1. Certifications	6
2.2. Pressure equipment directive	6
Device used on a pipe	6
3. Materials	6
3.1. Chemical Resistance Chart – Bürkert resistApp.....	6
4. Dimensions	7
4.1. Flowmeter with external thread pipe connection.....	7
4.2. Flowmeter with internal thread pipe connection.....	7
5. Product installation	8
5.1. Installation notes.....	8
6. Product operation	8
6.1. Measuring principle.....	8
7. Product accessories	8
8. Ordering information	9
8.1. Bürkert eShop – Easy ordering and quick delivery.....	9
8.2. Bürkert product filter	9
8.3. Ordering chart.....	9
8.4. Ordering chart accessories.....	10

1. General technical data

Product properties

Material

Make sure the device materials are compatible with the fluid you are using.

Detailed information can be found in chapter [“3.1. Chemical Resistance Chart – Bürkert resistApp”](#) on page 6.

Non wetted parts

Housing	Stainless steel 1.4404/316L, 1.4409/CF3M
Display	PC

Wetted parts

Pipe connection	Stainless steel 1.4404/316L
Measurement tube	PEEK
Electrode	Stainless steel 1.4435/316L
Temperature sensor	Stainless steel 1.4435/316L
Seal	FKM or EPDM

Display	1.4" TFT (thin-film-transistor) colour display with back-lighting, auto-rotatable (dependent on orientation)
---------	--

Pipe diameter	<ul style="list-style-type: none"> • DN 15...DN 50 • ½"...2"
---------------	--

Dimensions	Detailed information can be found in chapter “4. Dimensions” on page 7.
------------	---

Weight	<ul style="list-style-type: none"> • DN 15 (½"): 0.34 kg • DN 20 (¾"): 0.35 kg • DN 25 (1"): 0.36 kg • DN 50 (2"): 1.55 kg
--------	--

Measuring element	Electrodes
-------------------	------------

Measuring principle	Electromagnetic Detailed information can be found in chapter “6.1. Measuring principle” on page 8.
---------------------	---

Measured quantity	<ul style="list-style-type: none"> • Volume flow rate • Temperature • Conductivity¹⁾
-------------------	--

Measuring range

Volume flow rate measurement	<ul style="list-style-type: none"> • DN 15 (½"): 0.05...35 l/min (0.013...9.2 gal/min) • DN 20 (¾"): 0.1...75 l/min (0.026...19.8 gal/min) • DN 25 (1"): 0.2...150 l/min (0.052...39.6 gal/min) • DN 50 (2"): 1.5...750 l/min (0.4...198.1 gal/min)
------------------------------	---

Temperature measurement	-10...+70 °C (+14...+158 °F)
-------------------------	------------------------------

Conductivity measurement	<ul style="list-style-type: none"> • DN 15 (½"): 20...30 000 µS/cm • DN 20 (¾"): 20...30 000 µS/cm • DN 25 (1"): 20...30 000 µS/cm • DN 50 (2"): 20...10 000 µS/cm
--------------------------	--

Operating mode	<ul style="list-style-type: none"> • Via wireless technology via radio waves (Wireless Field Device Configurator application) • Via IO-Link
----------------	---

Performance data

Volume flow rate measurement

Under reference conditions i.e. measuring fluid = water, temperature = +15...+45 °C (+59...+113 °F) and pressure = 2...6 bar (29.00...87.02 PSI)

Measurement deviation	≤ (±0.8 % of the measured value) + (±0.1 % of full scale)
Repeatability	±0.2 % of the measured value

Temperature measurement

Measurement deviation	±2.5 °C (±4.5 °F)
Repeatability	±0.5 °C (±0.9 °F)
Response time (t90)	Typically 30 s

Conductivity measurement

Repeatability	(±5 % of the measured value) + (±5 µS/cm)
---------------	---

Current output uncertainty²⁾

Additional error	± 20 µA, at 25 °C ambient temperature
Repeatability	± 10 µA
Response time (t ₉₀)	Typically 200 ms

Voltage output uncertainty²⁾

Additional error	± 60 mV, at 25 °C ambient temperature
Repeatability	± 10 mV
Response time (t ₉₀)	Typically 200 ms

Electrical data

Operating voltage	18...30 V DC, filtered and regulated
Power source (not supplied)	Limited power source according to UL/EN 60950-1 standards or limited energy circuit according to UL/EN 61010-1 paragraph 9.4
DC reverse polarity protection	Yes
Overvoltage protection	Yes
Short circuit protection	Yes
Current consumption	<ul style="list-style-type: none"> Without outputs IO1 and IO2: 120 mA With outputs IO1 and IO2: 120 mA plus the effective load currents
Power consumption	Max. 3 W

Input/output

Digital input	<p>2 freely selectable inputs/outputs (IO1 and IO2)</p> <p>Status inputs (e.g. for a totalizer reset)</p> <ul style="list-style-type: none"> Minimum pulse duration: 100 ms High or low active Switch-on level: 15 V Switch-off level: 5 V Internal resistance: 7.5 kΩ
Digital output	<ul style="list-style-type: none"> Switch: <ul style="list-style-type: none"> PNP (high-side-switch) or NPN (low-side-switch) switching behaviour of IO1 and IO2: configurable independently of one another max. load current: 250 mA. Pulse: <ul style="list-style-type: none"> PNP (high-side-switch) only available for output 1 (IO1) max. load current: 250 mA. max. pulse rate: 10 000 Pulse/s IO-Link: <ul style="list-style-type: none"> only available for output 1 (IO1)
Analogue output	<ul style="list-style-type: none"> Current outputs (4...20 mA) <ul style="list-style-type: none"> The maximum load may not exceed 500 Ω. A bigger load distorts the output signal. Voltage output (2...10 V) <ul style="list-style-type: none"> The minimum load may exceed 600 Ω. A smaller load distorts the output signal.
Fault signal	<ul style="list-style-type: none"> Status signal (as per NAMUR Recommendation NE 107) Plain text display with remedial action
Connection cable	At least 0.12 mm ² (AWG26) cross-section

Medium data

Fluid temperature	<ul style="list-style-type: none"> -10...+70 °C (+14...+158 °F) Permissible short-term temperature: +85 °C (+185 °F) maximum one hour every four hours Permissible short-term temperature with electronics switched off: +100 °C (+212 °F) maximum one hour every four hours
Fluid pressure	Max. 16 bar (232 PSI), relative
Minimum conductivity	10 µS/cm

Process/Pipe connection & communication

Pipe connection	<ul style="list-style-type: none"> External thread G ½", G ¾", G 1" or G 2" Internal thread NPT ½", NPT ¾", NPT 1" or NPT 2"
Electrical connection	M12 × 1 A-coded, male

Digital communication: IO-Link

Communication interface	<ul style="list-style-type: none"> • IO-Link device V1.1 • IO-Link Smart Sensor Profile 2nd Edition
SIO mode	Yes
Baud rate (data transfer rate)	COM 2 (38.4 kBaud)
Cycle time	Min. 10 ms
Process data width	120 bit
IO-Link data storage	Yes
Block configuration	No
Device operational	Operational four seconds after the supply voltage is applied
IO device description (IODD)	The device description is available in the operating instructions which can be found on our website under the “User Manuals” heading for Type 8050 ▶. Alternatively, see “Device Description Files” under the “Software” heading for Type 8050 ▶ or at https://ioddfinder.io-link.com

Approvals and certificates

Directives

CE directive	The applied standards, which verify conformity with the EU Directives, can be found on the EU Type Examination Certificate and/or the EU Declaration of conformity (if applicable).
Pressure equipment directive	Complying with article 4, paragraph 1 of 2014/68/EU directive Detailed information on the pressure equipment directive can be found in chapter “2.2. Pressure equipment directive” on page 6.
Certification	UL Listed for US and Canada
Certificate	<ul style="list-style-type: none"> • UKCA marking On request: <ul style="list-style-type: none"> • Drinking water • Radio certification (for instance for Europe: Telecommunications Directive RED 2014/53/ EU and with other certifications in countries such as Argentina, Australia and New Zealand, Canada, United States, etc.)


Environment and installation

Ambient temperature	<ul style="list-style-type: none"> • Operation: - 10...+60 °C (+ 14...+140 °F) • Storage: - 25...+85 °C (- 13...+ 185 °F)
Relative air humidity	≤ 100 % (wet and damp locations)
Height above sea level	Max. 2000 m
Operating condition	Continuous
Equipment mobility	Fixed device
Application range	Indoor and outdoor Protect the device against electromagnetic interference, ultraviolet rays and against the effects of climatic conditions.
Degree of protection according to IEC/EN 60529	IP65/IP67
Installation category	Category II according to UL/EN 61010-1
Pollution degree	Degree 3 according to UL/EN 61010-1

- 1.) Conductivity measurement is possible with this device, but even if the measurement is reliable it is only indicative. The device must not be used as a conductivity meter.
2.) The deviation of the measurement at the outputs can increase depending on the device configuration.

2. Approvals

2.1. Certifications

Certification	Description
	UL Listed for USA and Canada The products are UL listed and also comply with the following standards: <ul style="list-style-type: none"> • UL 61010-1 • CAN/CSA-C22.2 No. 61010-1

2.2. Pressure equipment directive

The device conforms to article 4, paragraph 1 of the pressure equipment directive 2014/68/EU under the following conditions:

Device used on a pipe


Note:

- The data in the table is independent of the chemical compatibility of the material and the fluid.
- PS = maximum admissible pressure (in bar), DN = nominal diameter of the pipe

Type of fluid	Conditions
Fluid group 1, article 4, paragraph 1.c.i	$DN \leq 25$
Fluid group 2, article 4, paragraph 1.c.i	$DN \leq 32$ or $PS \cdot DN \leq 1000$
Fluid group 1, article 4, paragraph 1.c.ii	$DN \leq 25$ or $PS \cdot DN \leq 2000$
Fluid group 2, article 4, paragraph 1.c.ii	$DN \leq 200$ or $PS \leq 10$ or $PS \cdot DN \leq 5000$

3. Materials

3.1. Chemical Resistance Chart – Bürkert resistApp



Bürkert resistApp – Chemical Resistance Chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.


[Start Chemical Resistance Check](#)

4. Dimensions

4.1. Flowmeter with external thread pipe connection

Note:

Dimensions in mm, unless otherwise stated




DN	H	H1	L	L1	L2	L3	ø D	D1 [inch]	I	K
15	56	43	110	73	40.5	M12x1	12	G ½"	56	AF 24
20	56	43	110	73	40.5	M12x1	15	G ¾"	56	AF 27
25	56	43	110	73	40.5	M12x1	15	G 1"	56	AF 27
50	86	58	200	113	80	M12x1	43	G 2"	86	AF 52

4.2. Flowmeter with internal thread pipe connection

Note:

Dimensions in mm, unless otherwise stated



DN	H	H1	L	L1	L2	L3	L4	ø D	D1 [inch]	I	K
15	56	43	110	73	40.5	69.5	M12x1	29.5	NPT ½"	56	AF 27
20	56	43	110	73	40.5	69.5	M12x1	36	NPT ¾"	56	AF 32
25	56	43	110	73	40.5	69.5	M12x1	42	NPT 1"	56	AF 41
50	86	58	180	113	80	120	M12x1	73.5	NPT 2"	86	AF 70

DTS 1000540238 EN Version: A Status: RL (released | freigegeben | valide) printed: 16.06.2023

5. Product installation


5.1. Installation notes

Note:

The device is not suitable for use in gaseous media and steam.

- During flowmeter operation the pipe must be completely full.
- No upstream and downstream distances need to be considered.

The sensor can be installed into either horizontal or vertical pipes. All correct installation positions described in the following allow accurate flow measurement. However, we recommend that you install the sensor in an **ascending** pipe for optimal flow measurement.



6. Product operation

6.1. Measuring principle

Faraday's law serves as the physical basis for magnetic flow measurement.

Magnetic coils are arranged around the pipeline to generate a magnetic field. Conductive liquids flowing through the magnetic field induce a voltage at two opposite metallic electrodes in contact with the medium. These electrodes are used to measure the induced electrical alternating voltage.

7. Product accessories

Note:

- The installation of the flowmeter in a pipe requires the use of adapters and seals, depending on the device variant.
- The drawings show the assembly with both variants of the device.

See "8.4. Ordering chart accessories" on page 10 for more information.

Accessories	No.	Description
	1	Pipe with internal thread connection
	2	Seal (not supplied; use suitable commercially available seal material.)
	3	Adapter Detailed information can be found in chapter "8.4. Ordering chart accessories" on page 10.
	4	Seal (included in delivery, see also chapter "8.4. Ordering chart accessories" on page 10)
	5	External thread connection of the flowmeter
	1	Pipe with conical external thread connection
	2	Seal (not supplied; use suitable commercially available seal material.)
	3	Internal thread connection of the flowmeter

8. Ordering information

8.1. Bürkert eShop – Easy ordering and quick delivery



Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

8.2. Bürkert product filter



Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

8.3. Ordering chart




























Note:

The following variants have as minimum

- a pipe connection in stainless steel
- a measurement tube in PEEK
- electrodes and a temperature sensor in stainless steel

DN [mm]	Measuring range			Pipe connection	Seal material	Article no.
	Volume flow rate	Temperature	Conductivity			
Flowmeter with external (male) thread pipe connection						
15	0.05...35 l/min (0.013...9.2 gal/min)	- 10...+ 70 °C (+ 14...+ 158 °F)	20...30 000 µS/cm	G ½"	FKM EPDM	571164 571165
20	0.1...75 l/min (0.026...19.8 gal/min)		20...30 000 µS/cm	G ¾"	FKM EPDM	571172 571173
25	0.2...150 l/min (0.052...39.6 gal/min)		20...30 000 µS/cm	G 1"	FKM EPDM	571180 571181
50	1.5...750 l/min (0.4...198.1 gal/min)		20...10 000 µS/cm	G 2"	FKM EPDM	571188 571189
Flowmeter with internal (female) thread pipe connection						
15	0.05...35 l/min (0.013...9.2 gal/min)	- 10...+ 70 °C (+ 14...+ 158 °F)	20...30 000 µS/cm	NPT ½"	FKM EPDM	571166 571167
20	0.1...75 l/min (0.026...19.8 gal/min)		20...30 000 µS/cm	NPT ¾"	FKM EPDM	571174 571175
25	0.2...150 l/min (0.052...39.6 gal/min)		20...30 000 µS/cm	NPT 1"	FKM EPDM	571182 571183
50	1.5...750 l/min (0.4...198.1 gal/min)		20...10 000 µS/cm	NPT 2"	FKM EPDM	571190 571191

8.4. Ordering chart accessories

Description	Article no.	
Adapter set^{1.)} suitable for flowmeter with external thread pipe connection		
G 1/2" to G 3/8" male thread		571196 
G 1/2" to R 3/8" male thread		571197 
G 1/2" to G 1/2" female thread		571198 
G 1/2" to R 1/2" male thread		571199 
G 1/2" to 1/2" clamp, ø25 mm, BS4825 (similar DIN 32676 series C and ASME BPE)		571200 
G 3/4" to R 3/4" male thread		571201 
G 3/4" to G 3/4" female thread		571202 
G 3/4" to 3/4" clamp, ø25 mm, BS4825 (similar DIN 32676 series C and ASME BPE)		571203 
G 1" to R 1" male thread		571204 
G 1" to G 1" female thread		571205 
G 1" to 1" clamp, ø50 mm, BS4825 (similar DIN 32676 series C and ASME BPE)		571206 
G 2" to R 1 1/2" male thread		571207 
G 2" to R 2" male thread		571208 
G 2" to G 1 1/2" male thread		571209 
G 2" to G 2" female thread		571210 
G 2" to 2" clamp, ø64 mm, BS4825 (similar DIN 32676 series C and ASME BPE)		571211 
Seal set suitable for flowmeter with external thread pipe connection		
Seal in aramide fibre	DN 15	571218 
	DN 20	571219 
	DN 25	571220 
	DN 50	571221 
Electrical connection		
M12 straight circular female connector with cable, 4x0.34, in PUR (Polyurethane)	2 m	571222 
	5 m	571223 
	10 m	571224 
M12 angled (90°) circular female connector with cable, 4x0.34, in PUR (Polyurethane)	2 m	571225 
	5 m	571226 
	10 m	571227 
Ground terminal set		
Ground terminal		571217 

1.) The corresponding seal made from aramide fibre is also supplied.

Bürkert – Close to You

For up-to-date addresses
please visit us at
www.burkert.com

DTS 1000540238 EN Version: A Status: RL (released | freigegeben | validé) printed: 16.06.2023

