ZHONGSHAN Y-CHEN LIGHTING TECHNOLOGY CO.LTD

6F, 01B, No.28, Kanglong No.3Rd, Xinmao Industrial, Henglan Town, Zhongshan City

TECHNICAL DATASHEET FOR YC-T004

Date: 17.02.2025

DIMENSIONS			
	36W(+/-5W)	18W(+/-5W)	
Length	800mm	400mm	
Width	35mm	35mm	
Thickness	25mm	25mm	
INPUT PARAMETERS			
Power Consumption	36W/18W (+/-5W)		
Input Voltage Range	110-380V		
Input Frequency	50/60Hz		6
Power Factor / THD	>0.95 / <10%		
Power Efficiency	>88%		0
LED DRIVER			
LED Driver Type	Isolated Constant Current Driver		
LED Type and Make	PCT3030		
LED Efficiency	>140 lm/W		
LED CCT	2700K-6500K		
CRI	>70		
LUMINARY			
Luminary Efficacy	140 lm/W		
Working Environment	-20°C +40°C, Humidi	ty - 95% RH	
IP rating	IP66		
IK rating	IK08		
Rated Lamp Life (avarage	>50 000 hours		
Protection class	Class I		
FEATURES			

HIGH EFFICIENCY
ENERGY SAVING
MERCURY FREE AND NO UV
EASY INSTALLATION
COST EFFECTIVE

INDUSTRIAL LIGHTING
SHOPPING MALL LIGHTING
PARKS & PUBLIC MEETING PLACES
DOOR & OUTDOOR STADIUMS
FACTORIES & WORKSHOPS