

MB1S THRU MB10S


Voltage Range - 100 to 1000 V olts Current - 0.8 Ampere



SINGLE PHASE GLASS PASSIVATED BRIDGE RECTIFIERS

PINNING

PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



Features

- ◆ Ideal for printed circuit board
- ◆ Reliable low cost construction utilizing molded plastic technique
- ◆ High temperature soldering guaranteed: 260°/10 seconds at 5 lbs., (2.3kg) tension
- ◆ Small size, simple installation
- ◆ High surge current capability

Mechanical Data

- ◆ **Case** : JEDEC MBS Molded plastic body
- ◆ **Terminals** : Solder plated, solderable per MIL-STD-750, Method 2026
- ◆ **Polarity** : Polarity symbol marking on body
- ◆ **Mounting Position** : Any
- ◆ **Weight** : 0.008 ounce, 0.22 grams

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	MB1S	MB2S	MB4S	MB6S	MB8S	MB10S	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	100	200	400	600	800	1000	V
Maximum average forward rectified current at $T_c=30^\circ C$ On glass-epoxy P.C.B. On aluminum substrate	$I_{F(AV)}$				0.5 0.8			A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}				30			A
Maximum instantaneous forward voltage drop per leg at=0.4A	V_F				1.0			V
Maximum DC reverse current at rated DC blocking voltage $T_A=25^\circ C$ $T_A=125^\circ C$	I_R				5 0.5			μA mA
Typical junction capacitance (Note 3)	C_J				13			pF
Typical thermal resistance	$R_{\theta JC}$				70			$^\circ C/W$
Operating temperature range	T_J				-55 to +150			$^\circ C$
storage temperature range	T_{STG}				-55 to +150			$^\circ C$

NOTES:1.On glass epoxy P.C.B. mounted on 0.05x0.05"(1.3x1.3mm) pads

2.On aluminum substrate P.C.B. with on area of 0.8"x0.8"(20x20mm) mounted on 0.05X0.05"(1.3X1.3mm) solder pad

3.Measured at 1.0MHz and applied reverse voltage of 4.0 volts.

MB1S THRU MB10S

Voltage Range - 100 to 1000 V olts Current - 0.8 Ampere



Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



MB1S THRU MB10S


Voltage Range - 100 to 1000 V olts Current - 0.8 Ampere



PACKAGE OUTLINE

Plastic surface mounted package; 4 leads

MBS



The recommended mounting pad size

