

## CHINA LITHIUM PRODUCTS TECHNOLOGY CO.,LTD

## TECHNICAL DATA SHEET (TDS) OF MALEIC ANHYDRIDE

Version: 2.0 EN Revision Date: 2025-04

FORMULA: MA

APPEARANCE: WHITE CRYSTAL

**CAS NO.:** 108-31-6

APPLICATION: MALEIC ANHYDRIDE IS MAINLY USED AS RAW MATERIALS FOR THE

PRODUCTION OF UNSATURATED POLYESTER RESIN, ALKYD RESIN,

PESTICIDE MALATHION, HIGHLY EFFICIENT AND LOW TOXIC

PESTICIDE 4049, LONG-ACTING IODINE AMINE, ETC

**PRODUCT SPECIFICATIONS:** INDUSTRIAL STANDARD

MA % 99.45 MIN

RESIDUE ON IGNITION % 0.0049 MAX

MOLTEN COLOR(HAZEN) 24.99 MAX

MELTING POINT  $/^{\circ}$ C 52.4 MIN

IRON(FE)/(PPM) 1.95 MAX

PACKAGING: PACKED IN NET WEIGHT 25KG BAG

STORAGE: STORE IN A COOL, DRY, AND WELL VENTILATED WAREHOUSE. STAY

AWAY FROM SOURCES OF FIRE AND HEAT. KEEP THE CONTAINER SEALED. IT SHOULD BE STORED SEPARATELY FROM OXIDANTS, REDUCING AGENTS, ACIDS, AND EDIBLE CHEMICALS, AND AVOID MIXING STORAGE. EQUIP WITH CORRESPONDING TYPES AND QUANTITIES OF FIRE-FIGHTING EQUIPMENT. THE STORAGE AREA SHOULD BE EQUIPPED WITH SUITABLE MATERIALS TO CONTAIN

LEAKED MATERIALS.



E-mail: info@lithium-chemical.com

Http://www.lithium-chemical.com

Page No: 1 / 1

Authorised By: (QA Manager)- Wu Xia

