# 5" Coaxial Ceiling Speaker (30W/15W/7.5W/3.8W)

## FCS-630PH

#### Feature:


- ✓ Commercial public address system ceiling speaker with transformer.
- ✓ Hi-fi range coaxial ceiling loudspeaker with ABS cover.
- ✓ Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- ✓ Rated power output 30W/15W/7.5W/3.8W at 100V and 80hms
- ✓ 5" coaxial PP driver unit with 1" tweeter
- ✓ Line input 100V or 70V & 8  $\Omega$ .
- ✓ ABS enclosure, metal grille and ABS back cover in white.
- ✓ Flush mount in-ceiling quick and secure installation.
- ✓ Wide dispersion rang installation PA loudspeaker.





### Specification:

Model	FCS-630PH
Description	5" Coaxial Ceiling Speaker
Rated Power Output	30W/15W/7.5W/3.8W
Line Input	100V or 70V & 8 Ω
Frequency Response	80-20KHz
SPL(@1W/m)	88dB
Speaker Unit	5" coaxial PP driver with 1" tweeter
Cutout Size	210mm
Dimension	Ф240x155mm
Material	ABS enclosure, metal grille and metal back cover in white
Mounting Way	Flush mount in-ceiling quick and secure installation
Weight	1.96kg

### Side View & Dimension:







## SPL VS Angle & SPL VS Frequency Diagrams:

