

# 6 zone Remote Microphone FA-600XM

## DESCRIPTION

FA-600XM is a remote paging microphone work with FA-6120X series amplifier, which is of 6 zone paging features, its communication distance up to 600 meters through straight CAT6 cable, each amplifier capacity of connection up to 8 units of remote paging microphone, these microphone are connected hand-by hand. These 6 remote paging microphones could be pre-set different priorities by its dip switch. The remote paging microphone is direct power supplied by the amplifier.

### Features:

- RS485 remote paging microphone.
- Each microphone of 6 zone capacity.
- System support 8 remote microphones of loop connection.
- 6 zone selection buttons and all zone button.
- Two RJ45 ports for connection with FA-6120X amplifier and next remote mic
- Support PPT and normal paging two modes.
- CAT5 or CAT6 cable communication up to 600 meters.
- POE power supply from FA-6120X controller..



### Specifications:

Model	FA-600XM
Description	6 zone Remote Microphone
Power Consumption	3W
Zone Capacity	6 Zones
System Capacity	8 Remote microphones
Line Inputs	350mV, 10kΩ
Mic Input	5mV, 600Ω
Frequency Response	80Hz~16kHz
THD	1% at RMS,1KHz
S/N Ratio	>70dB
Operating Temp	-20 to +70
Power Supply	DC24V, ±20%
Humidity	<95% no condensation
Dimension	256(W)×149(H)×52(D) mm
Weight	1.5kg

### Rear Panel

