

6.5" Frameless Coaxial Ceiling Speaker (5W/10W/20W/40W) FCS-340H

Feature:


- ✓ Commercial public address system ceiling speaker with transformer.
- ✓ Hi-fi range coaxial ceiling loudspeaker with fire dome.
- ✓ Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- ✓ Rated power output 5W/10W/20W/40W at 100V and 8ohms
- ✓ 6.5" coaxial PP driver unit with 1" tweeter
- ✓ Line input 100V or 70V & 8 Ω .
- ✓ ABS enclosure, metal grille and metal back can in white.
- ✓ Flush mount in-ceiling quick and secure installation.
- ✓ Wide dispersion rang installation PA loudspeaker.



Specification:

Model	FCS-340H
Description	6.5" Coaxial Ceiling Speaker
Rated Power Output	5W/10W/20W/40W
Line Input	100V or 70V & 8 Ω
Frequency Response	80-18KHz
SPL(@1W/m)	89dB
Speaker Unit	6.5" coaxial PP driver with 1" tweeter
Cutout Size	218mm
Dimension	Φ 242x160mm
Material	ABS enclosure, metal grille and metal back can in black
Mounting Way	Flush mount in-ceiling quick and secure installation
Weight	2kg

Side View & Dimension:



SPL VS Angle & SPL VS Frequency Diagrams:

