8" Coaxial Ceiling Speaker (10W/20W/40W/80W) FCS-780H

Feature:

- ✓ Commercial public address system ceiling speaker with transformer.
- ✓ Hi-fi range coaxial ceiling loudspeaker with fire dome.
- ✓ Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- Rated power output 10W/20W/40W/80W at 100V and 80hms
- √ 8" coaxial PP driver unit with 1" tweeter
- ✓ Line input 100V or 70V & 8Ω .
- ✓ ABS enclosure, metal grille and metal back can.
- ✓ Flush mount in-ceiling quick and secure installation.
- ✓ Wide dispersion rang installation PA loudspeaker.



Specification:

Model	FCS-780H
Description	8" Coaxial Ceiling Speaker
Rated Power Output	10W/20W/40W/80W
Line Input	100V or 70V & 8 Ω
Frequency Response	70-20KHz
SPL(@1W/m)	96dB±3dB
Speaker Unit	8" coaxial PP driver with 1" tweeter
Cutout Size	290mm
Dimension	Ф320x275 mm
Material	ABS enclosure, metal grille and metal back
Mounting Way	Flush mount in-ceiling quick and secure installation
Weight	3.9kg

Side View & Dimension:





