



KEYEE MICROWAVE TECHNOLOGY CO., LTD.

Coaxial Termination

Keyee Microwave manufactures coaxial termination from DC-40GHz, which is used to absorb RF energy, improve circuit matching, and avoid signal reflection and interference. Available in different power handling, frequency range and coaxial connector.

For more information or any interested model, please contact our sales engineers.



Technical parameter

P/N	Average power(W)	Peak power(kW)	Frequency range(GHz)	VSWR	Coax. Connector	Impedance(Ohm)
KY124CT2SF	2	0.25	DC-12.4	1.2	SMA	50
KY400CT2SF	2	0.25	DC-40	1.3	SMA	50



KEYEE MICROWAVE TECHNOLOGY CO., LTD.

KY180CT2SF	2	0.25	DC-18	1.2	SMA	50
KY180CT10SF	10	0.5	DC-18	1.4	N,BNC,SMA,TNC,7/16	50
KY400CT5SF	5	0.5	DC-40	1.4	SMA	50
KY60CT2NF	2	0.5	DC-6	1.2	N,SMA,BNC,TNC,7/16	50
KY30CT2NF	2	1	DC-3	1.10	7/16 (M)	50
KY80CT2NF	2	0.5	DC-8	1.2	N(M)	50
KY60CT5NF	5	0.5	DC-6	1.3	N,BNC,SMA,TNC,7/16	50
KY180CT5NF	5	0.5	DC-18	1.2	N,BNC,SMA,TNC	50
KY60CT10NF	10	1	DC-6	1.2	N,BNC,SMA,TNC,7/16	50
KY100CT10NF	10	1	DC-10	1.4	N,SMA,BNC,TNC	50
KY60CT25NF	25	1	DC-6	1.2	SMA,N,7/16,TNC,BNC	50
KY100CT25NF	25	1	DC-10	1.4	N	50
KY180CT25NF	25	1	DC-18	1.3	N,SMA,TNC	50
KY60CT30NF	30	10	DC-6	1.2	N,SMA,7/16,TNC,BNC	50
KY100CT30NF	30	1	DC-10	1.3	N	50



KEYEE MICROWAVE TECHNOLOGY CO., LTD.

KY40CT50NF	50	10	DC-4	1.2	N,SMA,7/16,TNC	50
KY40CT50NF	50	10	DC-4	1.2	N,SMA,7/16,TNC	50
KY180CT50NF	80	1	DC-18	1.2	N	50
KY40CT80NF	80	10	DC-4	1.1	N,7/16,TNC	50
KY180CT50NF	50	5	DC-18	1.1	N,7/16,SMA	50
KY180CT50NF	50	1	DC-18	1.10	N,SMA	50
KY100CT50NF	50	1	DC-10	1.10	N	50
KY40CT100NF	100	10	DC-4	1.25	N,7/16	50
KY180CT100NF	100	5	DC-18	1.25	N	50
KY40CT150NF	150	10	DC-4	1.30	N,7/16	50
KY180CT150NF	150	10	DC-18	1.4	N	50
KY180CT150NF	150	5	DC-18	1.4	N	50
KY40CT200NF	200	10	DC-4	1.3	N,7/16	50
KY100CT200NF	200	5	DC-10	1.3	N,7/16	50
KY40CT250NF	200	10	DC-4	1.3	N,7/16	50



KEYEE MICROWAVE TECHNOLOGY CO., LTD.

KY100CT250NF	250	5	DC-10	1.3	N,7/16	50
KY40CT300NF	300	10	DC-4	1.4	N,7/16	50
KY100CT300NF	300	5	DC-10	1.4	N,7/16	50
KY40CT400NF	400	10	DC-4	1.45	N,7/16	50
KY100CT400NF	400	10	DC-10	1.5	N,7/16	50
KY40CT500NF	500	10	DC-4	1.4	N,7/16	50
KY40CT800NF	800	10	DC-4	1.45	N,7/16	50
KY40CT1000NF	1000	10	DC-4	1.4	N,7/16,L27	50
KY40CT1500NF	1500	10	DC-4	1.4	N,7/16,L27	50
KY40CT2000NF	2000	10	DC-4	1.4	N,7/16,L27	50
KY20CT1000NF	1000	50	DC-2	1.3	N,7/16,L27	50
KY20CT2000NF	2000	50	DC-2	1.3	N,7/16,L27	50
KY20CT3000NF	3000	50	DC-2	1.3	L27, 7/16,L36	50
KY10CT5000NF	5000	100	DC-1	1.4	L27, 7/16,L36	50
KY30CT1NF	1	0.5	DC-3	1.2	N,NBC	75



KEYEE MICROWAVE TECHNOLOGY CO., LTD.

Numbers in P/N	Indicate
KY	Key Microwave
124	Frequency range: DC-12.4
CT	Coaxial Termination
2	Power handling: 2W CW
SF(SMA female)	Coaxial connector type